

## केन्द्रीय माध्यमिक शिक्षा बोर्ड

(मानव संसाधन विकास मंत्रालय ,भारत सरकार के अधीन एक स्वायत्त संगठन)

"शिक्षा केन्द्र", 2, कम्युनिटी सेंटर, प्रीत विहार, दिल्ली-110092

### निविदा सूचना

मुख्यालय भवन, प्रीत विहार, दिल्ली में टैरेस पर पुराने एयर कुलिंग प्लांट रूम में व्यायाम शाला के निर्माण के कार्य के लिए प्रतिष्ठित एजेन्सियों से मुहरबंद निविदाएं आमंत्रित की जाती हैं। 2.5 लाख रुपये की लागत के अलग-अलग तीन कार्य अथवा 04.00 लाख रुपये की लागत के अलग-अलग दो कार्य अथवा उससे अधिक के कार्यों को पूरा करने वाली एजेंसियां ही आवेदन कर सकती हैं। निविदा फार्म की कीमत रु. 500/- एवं धरोहर राशि रु. 35,000/- (ईएमडी) का डीडी/बीडी जो सचिव, सीबीएसई के पक्ष में हो तथा अनुभव दस्तावेज संलग्न होने चाहिए। सीलबंद लिफाफों पर मुख्यालय भवन, प्रीत विहार, दिल्ली में टैरेस में पुराने एयर कुलिंग प्लांट रूम में व्यायाम शाला का निर्माण लिखा हो। निविदा दस्तावेज बोर्ड की वेबसाइट [www.cbse.nic.in](http://www.cbse.nic.in) से डाउनलोड किए जा सकते हैं। विधिवत रूप से भरी हुई निविदा रिसेप्शन काउंटर, केमाशिबो मुख्यालय, प्रीत विहार, दिल्ली-110092 के पास रखे निविदा बाक्स में दिनांक 22.07.2014 को 02.30 अप. बजे तक डाल देनी चाहिए। निविदा उसी दिन 03.00 बजे अप. में खोली जाएगी। सचिव, केमाशिबो को किसी या सभी निविदाओं को बिना कोई कारण बताए रद्द करने का अधिकार है।

संयुक्त सचिव (प्रशा. एवं विधि)

## **TENDER NOTICE**

Sealed tenders are invited from reputed agencies for the work of C/O Gymnasium in old Air Cooling Plant Room in Terrace at H.Q. bldg. Preet Vihar-Delhi. Agencies executed 3 works of value 2.5 lacs each or two works of value Rs.4 lacs or more may apply. Cost of tender documents Rs. 500/- & EMD amounting to Rs. 35000/- payable through DD/BD in f/o the Secretary, CBSE & experience documents must be annexed. Sealed envelopes of superscribed C/O Gymnasium in old Air Cooling Plant Room in Terrace at H.Q. bldg. Preet Vihar-Delhi. Tender documents can be downloaded from Board's Website: [www.cbse.nic.in](http://www.cbse.nic.in). Tender complete in all respect must be submitted latest by 22.07.2014 upto 2.30 p.m. and dropped in the tender-box placed at Reception Counter, HQ, Bldg. Preet Vihar, Delhi-110092. Tender would be opened at 3:00 p.m. or same day. Secretary CBSE has the right to reject any or all tender without assigning any reason.

**Joint Secretary (A& L)**

## Schedule of work

Name of work- C/O Gymnasium in old Air Cooling Plant Room in Terrace at H.Q. bldg. Preet Vihar-Delhi

SL No.	Description of Work	Qty	Unit	Rate	Amount
1.	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer in-charge.	8.5	cum		
2.	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	425	sqm		
3.	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :				
	(a) Of area 3 sq.metres and below	1	each		
	(b) Of area beyond 3 sq. metres	2	each		
5.	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level. (a) Cement mortar 1:4 (1 cement :4 coarse sand)	23	sqm		
6.	Providing and fixing tiled false ceiling of approved materials of size 595x595 mm in true horizontal level, suspended on interlocking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and				

	<p>cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanized butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge.</p> <p>(a) 8 mm thick fully perforated calcium silicate board made with Calcareous &amp; Siliceous materials reinforced with cellulose fiber manufactured through autoclaving process to give stable crystalline structure with minimum compressive strength 225 kg/sq. cm, bending strength 100 kg/sq. cm , of size 595x595 mm, having perforation of dia. 10 mm with minimum perforated area 18 % with non woven tissue on the back side, having an NRC ( Noise Reduction Coefficient) of 0.85, with 50 mm thick rockwool of 48 kg /cum backing.</p>	193	sqm		
7.	Providing and laying Vitrified tiles in floor with different sizes (thickness to be specified by the				

	<p>manufacturer), with water absorption less than 0.08% and conforming to IS:15622 , of approved brand &amp; manufacturer, in all colours and shade, laid with cement based high polymer modified quick set tile adhesive (water based) conforming to IS : 15477, in average 6 mm thickness, including grouting of joints (Payment for grouting of joints to be made separately).</p> <p>(a) Size of Tile 600x600 mm</p>	193	sqm		
8.	<p>12 mm cement plaster of mix : (a) 1:6 (1 cement: 6 fine sand)</p>	425	sqm		
9.	<p>Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.</p>	425	sqm		
10.	<p>Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface : (a) Water thinnable cement primer</p>	425	sqm		
11.	<p>Distempering with 1st quality acrylic distemper, having VOC (Volatile Organic Compound) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour. (a) Two coats</p>	425	sqm		
12.	<p>P&amp;F tube light fitting of size 595x595mm consisting of 3x36W CFL/ fitting complete n false ceiling of Philips, Crompton, Wipro make</p>	25	each		
13.	<p>Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top &amp; bottom pivot &amp; spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-in-charge (Door handle, lock and stopper etc.to be paid separately).</p>	7	sqm		

14.	P&F fittings like door handle lock and stoppers for frameless doors. Including floor spring etc complete	2	set		
15	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.  Group A Group B Group C	18 11 10	Point Point Point		
16	Wiring for power AC point with 4 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with modular switch, modular plate, suitable GI box and earthing the point with 4 sq.mm. FRLS PVC insulated copper conductor single core cable etc as required.	12	Point		
17	SITC of cassette type 2.0T single phase Air Conditioners including installation of voltas/itach or equivalent make.	05	nos		

## **Terms and Conditions**

1. The work should be executed as per CPWD specifications and as per directions of Engineer-In Charge.
2. The Completion time would be 45 days.
3. In case of delay, a penalty of 1% per week should be deducted.  
Subjected to a max of 5% of the tender value.
4. The measurement shall be done jointly by the Contractor and JE (Civil)
5. All T & P shall be arranged by the Contractor.
6. Hindrance Register shall be maintained by JE at site.
7. Instructions given in Site Order Book would be followed immediately.
8. Only one running payment would be considered after 40% Completion of work and subsequently thereafter final bill would be paid within 30 days after submission of bill by the contractor.
9. 10% of the bill shall be deducted as defect liability and shall be released after one year.
10. 25% deviation in quantities would be permitted.
11. Extra-item if any would be paid on analyzed markets rate but the work must be executed with prior approval of Engineer-in-charge.
12. In case of any dispute, the Arbitrator shall be appointed by the chairman and his decision shall be binding.
13. The material to be used must be got approved from the Engineer-In-Charge before installation/use.
14. Potable water shall only be used at site/work and arranged own self by the contractor. Nothing extra shall be paid on this account.
15. Arrangement shall be executed by the agency at its own cost.
16. The agency shall not delay/ stop the work without any valid reason.
17. In case of no/slow progress, the Board shall have the right to rescind the contract & get the work executed at the risk & cost of the defaulting agency.
18. Any material to be used on site shall be got checked & approved through the Engineer-In-Charge.

**(Signature of the Agency)**

**With complete address and seal**

Add. \_\_\_\_\_

Tel. No.: \_\_\_\_\_

Mobile No.: \_\_\_\_\_